

## Lubricant Oil/Cleaning Agents

### ◇A1 Tap Paste (cutting fluid for tap processing)

❗ Cannot be used for copper and copper alloys.



Name	Internal Capacity	Quantity Contained	¥	Delivery
A1T-25 Tap Paste 2.5K	2.5kg	1 can		○

### ◇New Machine Cleaner Super (a high-strength cleaning agent with a faint odor)



\* For cleaning the exterior of machinery and parts, for vehicles, and cleaning engine rooms.



❗ There is no rust-proofing effect in water-soluble liquids. Please use a separate rust-proofing treatment after use of metal surfaces which have not been coated.

❗ Please do not use to clean glass or aluminum.

### Attached 500mℓ Spray Gun Water Soluble

Name	Internal Capacity	Quantity Contained	¥	Delivery
New Machine Cleaner Super 4L	4ℓ	1 pc.		○
New Machine Cleaner Super 18ℓ	18ℓ	1 box		○

### ◇A1 Multi-EP Grease No. 2



\* Dedicated grease for use with the KANA standard coupling.

\* A multi-purpose type of grease of lithium soap base blended at extreme pressure, it is well suited for bearings that are subject to the high load accompanying impacts, or for sliding surfaces, for example.

Name	Internal Capacity	Quantity Contained	¥	Delivery
MBSG04 Grease EP No.2 0.4K	0.4kg	1 unit		●
MBSG05 Grease EP No.2 0.5K	0.5kg	1 pc.		●
MBSG25 Grease EP No.2 2.5K	2.5kg	1 can		○
Grease EP No.2 16K	16kg	1 can		○

### ◇High-Tac EP (industrial gear oil)



\* Viscosity: JIS K2001

Name	Viscosity	Internal Capacity	¥	Delivery
High-Tac EP100 20L	100	20L		○
High-Tac EP150 20L	150	20L		○
High-Tac EP220 20L	220	20L		○
High-Tac EP320 20L	320	20L		○



Name and Quantity and quantity of cases



● Same-day shipping ○ 3-day shipping

\* Single order system available



Please inquire with our sales offices for safety data sheets (SDS).